



# DATA CENTERS AND INTEGRATED ENERGY SYSTEMS: ON-SITE INTEGRATION

---

Dominik Franjo Dominković\*, Senior Researcher at DTU Compute; [dodo@dtu.dk](mailto:dodo@dtu.dk)

Rune G. Junker, assistant prof at DTU Compute


Daniela Guericke, assistant prof at DTU Compute

*\*presenter*

# Outline

- Intro:
  - data centers in the energy system
- About the project: Cool-Data
- Optimization method and case study description
- Future work
- Take-home messages


# Data centers in energy systems – no silo thinking



# Cool-data project

- 2.5 MEUR Danish national project
- Focusing on small and medium-sized data centres
- Integrating data centres to energy systems
- <https://cool-data.dtu.dk/>  
<https://www.linkedin.com/company/cool-data>

# What needs to be taken into account?




+ Capacity expansion / investments!

# Naviair

- A complex system
- 4 chillers, 4 free coolers, **2 ATES (aquifer thermal energy storage) systems**
- Approx. 2 GWh of yearly cooling demand
- 2.7 GWh of yearly heating demand
- PV on site
- Average cooling demand: 228 kW
- Waste heat currently rejected to the environment

# ATES system



• Source: [deltares.nl](http://deltares.nl)

# Optimization approach: MILP

- Goal: to minimize the total energy costs
  - Both heating and cooling
- Constraints:
  - to meet hourly energy demand
  - To balance the usage of the ATES storage
- Decision variable:
  - Optimal investment in heat pumps in blocks 4 and 5




# The system

- 2 x 230 kW free coolers
  - 2 x 250 kW electric chillers
  - 230 kW ATES system
  - District heating (gas) covering the heat demand
- } Block 4 and block 5

Optimization of the capacity in a heat pump:


	Option 1	Option 2	Option 3	Option 4
capacity (kW)	120	160	200	240
Heat pump cost	500,000	650,000	800,000	950,000
Installation cost (fixed)	700,000	700,000	700,000	700,000
Total (DKK)	1,200,000	1,350,000	1,500,000	1,650,000
DKK/kW	10,001	8,439	7,501	6,876
Heat pump CAPEX per year DKK	48,171	62,622	77,074	91,525



# Naviair recommendation

- Coupling different energy systems on site!
- Recommended installation of 2 heat pumps: 200 and 240 kW
  - Covering 75% of the heating needs
- Payback period: 6.5 years
- NPV: 262 kEUR, IRR: 13%
- Yearly savings: 28.6 kEUR


To successfully utilize ATEs, heat and cooling extracted during the year need to be balanced out



# More on results

- Gas consumption reduction of 76% (3.1 GWh to 0.75 GWh)
- CO2 emissions reduction by 50% (658 to 331 tons)
- electricity consumption: 347 to 847 MWh (+ 2.4 times)

# Cooling operation – before HPs



# Cooling operation – after HPs



- Heat pumps allow for larger utilization of ATES storage – yearly balance!

# KPIs report is free to download



Innovation Fund Denmark

## New performance indicators for fully integrated and decarbonized data centres



<https://doi.org/10.11581/DTU:00000112>

## TABLE OF CONTENTS

Introduction	9
1 Integrated data centres to meet decarbonization targets	11
1.1. A key actor at the interface between electricity and heat	
1.2. The five dimensions of decarbonization	
2 Key performance indicators for energy use in integrated data centres	14
2.1. KPIs issued by standardization agencies and KPIs commonly used in the industry	
2.2. How do current indicators support decarbonization in data centres?	
2.3. Development of new indicators	
2.4. How do the new indicators support decarbonization in data centres?	
2.5. The way forward: two technical preconditions and three economic factors	
3 European initiatives to decouple data-centre growth from CO2 emissions	31
3.1. European Code of Conduct for Data Centre Energy Efficiency initiative.	
3.2. Climate Neutral Data Center Pact	
Conclusion	36
APPENDIX - Example of good practices	37
Bibliography	39

# Future work

- Stochastic optimization
  - Uncertainty from different possible climate scenarios: heating demand and PV generation
  - Electricity prices
- Developing optimal controllers
- Searching for advanced cooling strategies based on reinforcement learning

# Take home messages

- Holistic integration of data centers to energy systems
- If integration of heating and cooling load is possible: very efficient solutions possible
- Waste heat should be reused first on site and only then in district heating





---

COOL-DATA DEVELOPS, ASSESSES AND IMPLEMENTS AN AI-BASED MODULAR, FLEXIBLE, SECURE AND RELIABLE INTEGRATED COOLING ENERGY SYSTEM FOR DATA CENTRES.

- 1 ) THE PROJECT RECEIVED FUNDING FROM INNOVATION FUND DENMARK, COOL-DATA: FLEXIBLE COOLING OF DATA CENTERS
- 2) THE WORK WAS ALSO FUNDED BY THE IEA TS4: DIGITALIZATION OF DISTRICT HEATING PROJECT, FUNDED BY THE EUDP IN DENMARK



# Cool-Data

<https://cool-data.dtu.dk/>

<https://www.linkedin.com/company/cool-data>

direct contact: [dodo@dtu.dk](mailto:dodo@dtu.dk)